



CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: 270201

Issue date: 18.01.2017 Revision date: 16.08.2023 Supersedes version of: 01.02.2021 Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: CaluClean V53 graffiti remover
UFI	: 3ETF-KNS6-K30N-R9QM
Product code	: 23826
Type of product	: Detergent
Product group	: Cleaning product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Professional use
Industrial/Professional use spec	: Wide dispersive use
Use of the substance/mixture	: The information given in this MSDS concerns the product and is given on the assumption mentioned in section 1.1, that the product will be used in the manner and for the purposes indicated by the manufacturer.
Use of the substance/mixture	: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)
Function or use category	: Cleaning/washing agents and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor

Carel Lurvink Logistics B.V.

IJzersteden, 11

NL- 7547 TB Enschede

Nederland

T +31 (0)53-4344343 - F +31 (0)53-4337105

info@carellurvink.nl - www.carellurvink.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 2 H319

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Causes serious eye irritation.

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) : Warning.
Hazard statements (CLP) : H319 - Causes serious eye irritation.
Precautionary statements (CLP) : P280 - Wear eye protection, protective gloves.
P337+P313 - If eye irritation persists: Get medical advice/attention.
EUH-statements : EUH210 - Safety data sheet available on request.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-Methoxy-2-propanol substance with national workplace exposure limit(s) (IE, GB); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
Triethanolamine substance with national workplace exposure limit(s) (IE)	CAS-No.: 102-71-6 REACH-no: 01-2119486482-31	5 – 10	Not classified
Diethanolamine substance with national workplace exposure limit(s) (IE)	CAS-No.: 111-42-2 EC-No.: 203-868-0 EC Index-No.: 603-071-00-1 REACH-no: 01-2119488930-28	0,01 – 0,1	Acute Tox. 4 (Oral), H302 STOT RE 2, H373 Skin Irrit. 2, H315 Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : If you feel unwell, seek medical advice.

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking. Contact during a long period may cause light irritation.
- Symptoms/effects after eye contact : Eye irritation.
- Symptoms/effects after ingestion : May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool.
- Storage temperature : 10 – 30 °C

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Storage area	: Store away from heat. Keep storage area clean. Ensure that there is a suitable ventilation system.
Special rules on packaging	: Store in a closed container. Keep only in original container.

7.3. Specific end use(s)

Carefully comply with the instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

1-Methoxy-2-propanol (107-98-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	1-Methoxypropanol-2
IOEL TWA	375 mg/m ³
IOEL TWA [ppm]	100 ppm
IOEL STEL	568 mg/m ³
IOEL STEL [ppm]	150 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	Propylene glycol monomethyl ether [1-Methoxypropan2-ol]
OEL TWA [1]	375 mg/m ³
OEL TWA [2]	100 ppm
OEL STEL	568 mg/m ³
OEL STEL [ppm]	150 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropan-2-ol
WEL TWA (OEL TWA) [1]	375 mg/m ³
WEL TWA (OEL TWA) [2]	100 ppm
WEL STEL (OEL STEL)	560 mg/m ³
WEL STEL (OEL STEL) [ppm]	150 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Triethanolamine (102-71-6)	
Ireland - Occupational Exposure Limits	
Local name	Triethanolamine
OEL TWA [1]	5 mg/m ³
Regulatory reference	Chemical Agents Code of Practice 2021

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diethanolamine (111-42-2)	
Ireland - Occupational Exposure Limits	
Local name	Diethanolamine [2,2'-Iminodiethanol]
OEL TWA [1]	1 mg/m ³ IFV (Inhale Fraction and Vapour)
OEL TWA [2]	0,2 ppm
Regulatory reference	Chemical Agents Code of Practice 2021

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Triethanolamine (102-71-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	6,3 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	5 mg/m ³
Long-term - local effects, inhalation	5 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	13 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1,25 mg/m ³
Long-term - systemic effects, dermal	3,1 mg/kg bodyweight/day
Long-term - local effects, inhalation	1,25 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,32 mg/l
PNEC aqua (marine water)	0,032 mg/l
PNEC aqua (intermittent, freshwater)	5,12 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1,7 mg/kg dwt
PNEC sediment (marine water)	0,17 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,151 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4	2 (< 1.5)	EN 374-2

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Carefully comply with the instructions for use. Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow.
Appearance	: Clear.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 72 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 14285,714 mm ² /s

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Viscosity, dynamic	: 15000 mPa·s
Solubility	: In water, the material disperses.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1,05 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

1-Methoxy-2-propanol (107-98-2)	
LD50 oral	3739 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat (Dust/Mist)	> 26315 mg/l
Triethanolamine (102-71-6)	
LD50 oral	8000 mg/kg bodyweight
LD50 dermal	> 10000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 1,8 mg/l

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Diethanolamine (111-42-2)

LD50 oral	710 mg/kg bodyweight
LD50 dermal	12200 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Diethanolamine (111-42-2)

NOAEL (chronic, oral, animal/male, 2 years)	64 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 451 (Carcinogenicity Studies)
---------------------------------------------	------------------------------------------------------------------------------------------------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

1-Methoxy-2-propanol (107-98-2)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

1-Methoxy-2-propanol (107-98-2)

LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Diethanolamine (111-42-2)

LOAEL (dermal, rat/rabbit, 90 days)	32 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0,003 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
-------------------	------------------

CaluClean V53 graffiti remover

Viscosity, kinematic	14285,714 mm ² /s
----------------------	------------------------------

1-Methoxy-2-propanol (107-98-2)

Viscosity, kinematic	1,848 mm ² /s
----------------------	--------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-Methoxy-2-propanol (107-98-2)	
LC50 - Fish [1]	> 4600 mg/l
EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:Acartia tonsa
EC50 - Other aquatic organisms [2]	> 500 mg/l
Triethanolamine (102-71-6)	
LC50 - Fish [1]	11800 mg/l
EC50 - Other aquatic organisms [1]	2038 mg/l waterflea
EC50 - Other aquatic organisms [2]	216 mg/l
ErC50 algae	512 mg/l
Diethanolamine (111-42-2)	
LC50 - Fish [1]	460 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [2]	89,9 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	1,56 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,78 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

CaluClean V53 graffiti remover	
Persistence and degradability	The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Triethanolamine (102-71-6)	
Biochemical oxygen demand (BOD)	0,02 g O ₂ /g substance
Chemical oxygen demand (COD)	1,5 g O ₂ /g substance
ThOD	2,04 g O ₂ /g substance
BOD (% of ThOD)	0,02 % ThOD

12.3. Bioaccumulative potential

1-Methoxy-2-propanol (107-98-2)	
Partition coefficient n-octanol/water (Log Pow)	-0,49
Triethanolamine (102-71-6)	
Bioconcentration factor (BCF REACH)	< 3,9
Partition coefficient n-octanol/water (Log Pow)	-2,3
Diethanolamine (111-42-2)	
Partition coefficient n-octanol/water (Log Pow)	-1,4

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Empty containers can be dumped after cleaning according to local legislation. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 20 01 29* - detergents containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Detergent Regulation (648/2004)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Flammability (solid, gas)	Added	
	Supersedes	Modified	
	Revision date	Modified	
1.1	Name	Modified	
1.1	UFI on SDS 1.1	Added	
1.2	Main use category	Modified	
4.1	First-aid measures after ingestion	Modified	
4.1	First-aid measures after skin contact	Added	
4.2	Symptoms/effects after skin contact	Added	
4.2	Symptoms/effects after ingestion	Added	
5.1	Suitable extinguishing media	Modified	

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
5.2	Hazardous decomposition products in case of fire	Modified	
6.1	Protective equipment	Added	
6.3	Methods for cleaning up	Added	
6.4	Reference to other sections (8, 13)	Modified	
9.1	Melting point	Added	
9.1	Flash point	Added	
9.1	Solubility	Modified	
16	Abbreviations and acronyms	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	Sewage treatment plant
TLM	Median Tolerance Limit
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
BLV	Biological limit value

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
EC-No.	European Community number
EN	European Standard
OEL	Occupational Exposure Limit
ThOD	Theoretical oxygen demand (ThOD)
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
ED	Endocrine disrupting properties

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: None. DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Eye Irrit. 2	H319	Expert judgement
--------------	------	------------------

The classification complies with : ATP 8

CaluClean V53 graffiti remover

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.