



CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830
Reference number: 270214

Issue date: 18-1-2017 Revision date: 29-1-2021 Supersedes version of: 3-7-2019 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : CaluClean F4 industriële vloerreiniger
UFI : AJUF-5NRC-K302-CR9F
Product code : 3040025, 3035005
Type of product : Detergent
Product group : Cleaning product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use
Industrial/Professional use spec : Wide dispersive use
Use of the substance/mixture : The information given in this MSDS concerns the product and is given on the assumption mentioned in section 1.1, that the product will be used in the manner and for the purposes indicated by the manufacturer.
Use of the substance/mixture : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners, air fresheners)
Function or use category : Cleaning/washing agents and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor

Carel Lurvink Logistics B.V.
IJzesteden 11
7547 TB Enschede - Nederland
T +31 (0)53-4344343 - F +31 (0)53-4337105
info@carellurvink.nl - www.carellurvink.nl

1.4. Emergency telephone number

Emergency number : +31(0)534344343

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. Causes serious eye irritation.

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning.

Hazard statements (CLP) :

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

Precautionary statements (CLP) :

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear eye protection, protective gloves.

P337+P313 - If eye irritation persists: Get medical advice/attention.

EUH-statements :

EUH210 - Safety data sheet available on request.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Butoxyethanol substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	(CAS-No.) 111-76-2 (EC Index-No.) 603-014-00-0 (REACH-no) 01-2119475108-36	5 – 10	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Irrit. 2, H315
C9-11 PARETH-6	(CAS-No.) 68439-46-3 (EC-No.) 931-514-1 (REACH-no) Polymer	1 – 5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Tetrapotassiumpyrophosphate	(CAS-No.) 7320-34-5 (EC-No.) 230-785-7 (REACH-no) 01-2119489369-18	1 – 5	Eye Irrit. 2, H319
Isotridecanol, ethoxylated (8 EO)	(CAS-No.) 9043-30-5 (EC-No.) 500-027-2 (REACH-no) 02-2119552461-55	1 – 5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
Potassium hydroxide substance with national workplace exposure limit(s) (GB)	(CAS-No.) 1310-58-3 (EC-No.) 215-181-3 (EC Index-No.) 019-002-00-8 (REACH-no) 01-2119487136-33	0,1 – 1	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Potassium hydroxide	(CAS-No.) 1310-58-3 (EC-No.) 215-181-3 (EC Index-No.) 019-002-00-8 (REACH-no) 01-2119487136-33	(0,5 ≤C < 2) Eye Irrit. 2, H319 (0,5 ≤C < 2) Skin Irrit. 2, H315 (2 ≤C < 5) Skin Corr. 1B, H314 (5 ≤C < 100) Skin Corr. 1A, H314

Full text of H-statements: see section 16

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Other information	: Dispose of materials or solid residues at an authorized site.
-------------------	---

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool.
- Storage temperature : 10 – 30 °C
- Storage area : Store away from heat. Keep storage area clean. Ensure that there is a suitable ventilation system.
- Special rules on packaging : Store in a closed container. Keep only in original container.

7.3. Specific end use(s)

Carefully comply with the instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Potassium hydroxide (1310-58-3)	
United Kingdom - Occupational Exposure Limits	
Local name	Potassium hydroxide
WEL STEL (OEL STEL)	2 mg/m ³

2-Butoxyethanol (111-76-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Butoxyethanol
IOEL TWA	98 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	246 mg/m ³
IOEL STEL [ppm]	50 ppm
Notes	Skin
United Kingdom - Occupational Exposure Limits	
Local name	2-Butoxyethanol
WEL TWA (OEL TWA) [1]	123 mg/m ³
WEL TWA (OEL TWA) [2]	25 ppm
WEL STEL (OEL STEL)	246 mg/m ³
WEL STEL (OEL STEL) [ppm]	50 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2)

8.1.2. Recommended monitoring procedures

No additional information available

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

DL-Alanine-N,N-diacetic acid trisodium salt (164462-16-2)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	2000 mg/kg bodyweight/day
Acute - systemic effects, inhalation	40 mg/m ³
Acute - local effects, inhalation	40 mg/m ³
Long-term - systemic effects, dermal	170 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	40 mg/m ³
Long-term - local effects, inhalation	4 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	40 mg/kg bodyweight
Acute - systemic effects, inhalation	20 mg/m ³
Acute - systemic effects, oral	85 mg/kg bodyweight
Acute - local effects, dermal	400 mg/cm ²
Acute - local effects, inhalation	20 mg/m ³
Long-term - systemic effects, oral	17 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	20 mg/m ³
Long-term - systemic effects, dermal	25 mg/kg bodyweight/day
Long-term - local effects, inhalation	2 mg/m ³
PNEC (Soil)	
PNEC soil	2,5 mg/kg dwt

Potassium hydroxide (1310-58-3)	
DNEL/DMEL (Workers)	
Long-term - local effects, inhalation	1 mg/m ³
DNEL/DMEL (General population)	
Long-term - local effects, inhalation	1 mg/m ³

2-Butoxyethanol (111-76-2)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	≈ 125 mg/kg bodyweight/day
Acute - systemic effects, inhalation	≈ 1091 mg/m ³
Acute - local effects, inhalation	≈ 246 mg/m ³
Long-term - systemic effects, dermal	≈ 125 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	≈ 98 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	≈ 89 mg/kg bodyweight
Acute - systemic effects, inhalation	≈ 426
Acute - systemic effects, oral	≈ 26,7 mg/kg bodyweight
Acute - local effects, inhalation	≈ 147 mg/m ³

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

Long-term - systemic effects, oral	≈ 6,3 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	≈ 59 mg/m ³
Long-term - systemic effects, dermal	≈ 75 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	8,8 mg/l
PNEC aqua (marine water)	0,88 mg/l
PNEC aqua (intermittent, freshwater)	9,1 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	34,6 mg/kg dwt
PNEC sediment (marine water)	3,46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2,33 mg/kg dwt

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:			
Safety glasses			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:					
Protective gloves					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4	2 (< 1.5)	EN 374-2

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Carefully comply with the instructions for use. Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Appearance	: Clear to cloudy.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 100 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 13
Viscosity, kinematic	: < 19,324 mm ² /s
Viscosity, dynamic	: < 20 mPa·s
Solubility	: completely soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 1,035 g/cm ³
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Isotridecanol, ethoxylated (8 EO) (9043-30-5)

LD50 oral	> 500 mg/kg bodyweight
LD50 dermal	> 2000 mg/kg bodyweight

Potassium hydroxide (1310-58-3)

LD50 oral	333 mg/kg bodyweight
-----------	----------------------

2-Butoxyethanol (111-76-2)

LD50 oral	1746 mg/kg bodyweight
LD50 dermal	435 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	2200 mg/l

Tetrapotassiumpyrophosphate (7320-34-5)

LD50 oral	4640 mg/kg bodyweight
LD50 dermal	> 4640 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 1100 mg/l

Skin corrosion/irritation : Causes skin irritation.
pH: 13
Serious eye damage/irritation : Causes serious eye irritation.
pH: 13
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

CaluClean F4 industriële vloerreiniger	
Viscosity, kinematic	< 19,324 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Potassium hydroxide (1310-58-3)	
LC50 - Fish [1]	80 mg/l

2-Butoxyethanol (111-76-2)	
LC50 - Fish [1]	1474 mg/l
EC50 - Other aquatic organisms [1]	1550 mg/l waterflea
EC50 - Other aquatic organisms [2]	911 mg/l

Tetrapotassiumpyrophosphate (7320-34-5)	
EC50 - Other aquatic organisms [1]	100 mg/l EC50 waterflea (48 h)

12.2. Persistence and degradability

CaluClean F4 industriële vloerreiniger	
Persistence and degradability	The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Isotridecanol, ethoxylated (8 EO) (9043-30-5)	
Persistence and degradability	The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

Potassium hydroxide (1310-58-3)	
Partition coefficient n-octanol/water (Log Pow)	0,75

2-Butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water (Log Pow)	0,81

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

Tetrapotassiumpyrophosphate (7320-34-5)

Partition coefficient n-octanol/water (Log Pow) -10,45

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Empty containers can be dumped after cleaning according to local legislation. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations.
Ecology - waste materials : Avoid release to the environment.
European List of Waste (LoW) code : 20 01 29* - detergents containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Detergent Regulation (648/2004/EC): Labelling of contents:	
Component	%
anionic surfactants, non-ionic surfactants, phosphates	<5%
Methylchloroisothiazolinone, Methylisothiazolinone	
Methylisothiazolinone	
perfumes	

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
	SDS Ref.	Added	
1.1	Product code	Modified	
2.2	Precautionary statements (CLP)	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	Sewage treatment plant
TLM	Median Tolerance Limit
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None. **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2

CaluClean F4 industriële vloerreiniger

Safety Data Sheet

according to Regulation (EU) 2015/830

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
EUH210	Safety data sheet available on request.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Irrit. 2	H315	Expert judgment
Eye Irrit. 2	H319	Expert judgment

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.