



ALLE PRODUCTEN VINDT U OP WWW.CARELLURVINK.NL

Product niet gevonden? Bel +31 (0) 53 434 43 43



Dif product is verkrijgbaar bij carel Lurvink B.V. This product is available at carel Lurvink B.V.

Marssteden 40 | 7547 TC Enschede | NL Franciscusweg 281 | 1216 SG Hilversum | NL

WWW.CARELLURVINK.NL



SCHOONMAAKBEDRIJVEN

VOEDING & FARMACIE

INDUSTRIE & BOUW

GEZONDHEIDSSECTOR

RECREATIE & VRIJE TIJD

OVERHEID

VEILIGHEIDSBLAD

ledereen Verdienf een schone & Veilige werkomgeving

3M Citrus Based Industrial Cleaner

Product Data Sheet

Updated : November 1993 Supersedes : April 1992

Product Description

3M Industrial Cleaner is a heavy duty cleaner/ degreaser that works effectively on difficult to remove substances such as many dried, non-curing adhesives, tape residues, grease, oils and dirt. The cleaner is based on a citrus oil and does not contain chlorinated compounds or petroleum distillate solvents.

The cleaner emulsifies when flushed with water.

Physical Properties Not for specification purposes	Base	Citrus Based Oil
	Flash Point	-46°C
	Propellant	Propane
	Solids Content	0%
	Colour	Clear
	Shelf Life	12 months from date of despatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity

Performance Characteristics

Not for specification purposes

As a general guide to the effectiveness of 3M Industrial Cleaner, the following shows the performance in removing a range of 3M Tapes and Adhesive products.

- Key: 1 Excellent 2 Good 3 Average
 - 4 Difficult
 - 5 Not Suitable
 - 5 Not Suitable

Adhesive/Tape	Effectiveness	
	Wet	Cured
Neoprene:		
FASTBOND 10 Adhesive	2	3
Scotch-Grip Rubber Adhesive 1888V	3	4
Scotch-Grip Spray Adhesive 80	2	3
Nitrile:		
Scotch-Grip Vinyl Adhesive 1099	3	4

Date : November 1993 3M Industrial Cleaner

Adhesive/Tape	Effectiveness	
	Wet	Cured
SBR:		
Scotch-Grip Spray Adhesive 76	1	2
Scotch-Grip Spray Adhesive 90	1	2
Scotch-Grip Spray Adhesive 77	1	2
Scotch-Grip Insulation Adhesive 34	1	2
Acrylic Tape:		
927 Adhesive Transfer Tape	3	3
465 Adhesive Transfer Tape	3	3
Acrylic (Thermoset):		
Scotch-Weld Adhesive DP801	2	5
Epoxy (Thermoset):		
Scotch-Weld Structural Adhesive 2216 B/A	1	5
Polyurethane (Thermoset):		
Scotch-Weld Structural Adhesive 3532 B/A	2	5
Scotch-Weld Cyanoacrylate Adhesive E1100	2	5
Ethyl Vinyl Acetate:		
Jet-melt Adhesive 3792	5	5
Jet-melt Adhesive 3738	5	5
Synthetic Rubber Tape:		
9308 UPVC Carrier Rubber Adhesive	2	2

Application Characteristics

Adhesive Removal: When adhesives are still wet/uncured they will be easier to remove than when the adhesives have thoroughly dried or cured.

3M Industrial Cleaner is **Directions for Use** Shake can well, for at least Wait for a few minutes for applied in a similar way to 5 seconds. complete penetration and most aerosol products. loosening action. Turn Spray tip so arrow Test for suitability on all points to dot on can rim. Wipe thoroughly with a surfaces before full use. clean cloth (if desired, wipe Thoroughly coat all grease, with a damp cloth or rinse surface with water). Best results are obtained grime, etc. on the surfaces when product is at room or parts being cleaned. temperature. NB: When removing adhesives it may be necessary to repeat application.

			3M Industrial Cleaner
Additional Product Information	The surfactant in 3M Industrial Cleaner complies with the EEC biodegradability requirements for non-ionic surfactants as laid down in Directive 82/242/EEC.	Does not contribute to ozone depletion.	For additional information please contact your local 3M Sales Representative via the Manchester Sales Office below.
Health and Safety Information	Precautions: Highly flammable. Irritating to skin. May cause eye and respiratory irritation. Keep away from sources of ignition - No Smoking. Avoid prolonged breathing of vapours/spray. Use only in well ventilated areas. Avoid prolonged or repeated contact with the skin. Do not spray directly into eyes. Keep out of reach of children!	First Aid: Eye Contact: Rinse immediately with plenty of water and seek medical advice. Skin Contact: Wash with soap and water.	WARNING! Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on naked flame or incandescent material. For further Health and Safety information, please contact the Toxicology Department at Bracknell Head Office on (0344) 858000.

3M is a trademark of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.

3M Ireland

Ireland

3M House, Adelphi Centre,

Dun Laoghaire, Co. Dublin,

Upper Georges Street,

This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Specialty Tapes & Adhesives

3M United Kingdom PLC 3M House, 28 Great Jackson Street, Manchester, M15 4PA

Customer Service :

Tel0161 236 8500Fax0161 237 1105

© 3M United Kingdom PLC 1996

Customer Service :

Tel (01) 280 3555 Fax (01) 280 3509

Date : November 1993